

UKCA
DECLARATION OF CONFORMITY
N. 5-UKCA

1. Unique identification code of the product type:

DRY-PRESSED CERAMIC TILES, WITH WATER ABSORPTION E > 10%

2. Intended use or uses:

FOR INTERNAL WALLS

3. Name or registered trade mark, and contact address of the manufacturer:

KERABEN GRUPO S.A.U. Ctra. Valencia-Barcelona Km 44,3 12520 Nules (Castellón) España

4. System o systems of assessment and verification of constancy of performance:

System 4

5. Name and identification number of notified laboratory: **Not applicable**

6. Declared performances:

Essential characteristics		Performance	Harmonised technical specification
Reaction to fire (Decision 96/603/EEC amended)		Class A1	BS EN 14411
Adhesion with cement adhesive type		Class C1: $\geq 0,5 \text{ N/mm}^2$	
Emissions of dangerous substances (Cadmium/lead emissions)		NPD	
Durability for	Internal use	Complies	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of conformity is issued under the sole responsibility of the manufacturer identified in point 3.

NPD: No Performance Determined

- Please check before fixing: model, shade, calibre and quality. Do not mix calibers.
- In complementary special pieces where metals have been used (gold, silver, copper,...), lustres, mashing, resins, glass, etc., may present certain characteristics (slight variations in shade, oxidation on contact with air and moisture, aged appearance with the passage of time...).
- Rectified and/or meshed materials require handling with care to prevent chipping on their edges and surface scratches.
- The complementary special pieces PEBIII-001 are not suitable for exterior installation.
- **CLEANING OF WORK:** Avoid the hardening of the adhesive material on the piece (clean before 24 hours). Remove the remnants of adhesive (cements, String, etc.) with a sponge and plentiful water. Not use any abrasive product or application with acidic or alkaline base, to avoid any loss of appearance or surface attack. Do not use products with hydrochloric acid nor cleaning pads.
- **MAINTENANCE:** in the cleaning of tiles, not use powder detergents, neither acidic nor alkaline solutions, neither cleaning pads nor abrasive elements. It is enough to use a neutral liquid soap and a wet cloth.
- Laying the tiles means that they have been accepted, and, as a result, no claims will be accepted for material installed, arising from a failure to comply with these premises.

KERABEN GRUPO

KERABEN GRUPO, S.A.U.



Ricardo Martínez Rodríguez
Director of Quality Department